

INSIEME



Housing: Pendant with light distribution up, out and down. 3 circular aluminum profiles, with integrated acrylic covers.

Design: MARKUS BISCHOF



	Size: Ø mm	inches	LED Watt	Lumen ¹⁾	weight kg ²⁾ / lbs ²⁾	Item No.	LED	Dimming	LED	Finishes	Power Supply cable	Mounting Version	
Sizes	Ø 900 mm	35.4"	165	8.163	5.0 / 11.0	762.	x x .	x x .	x x .	x x .	x x x .	x	
	Ø 1240 mm	48.8"	216	10.680	7.0 / 15.4	765.	x x .	x x .	x x .	x x .	x x x .	x	
	Ø 1550 mm	61.0"	264	12.338	9.0 / 19.8	766.	x x .	x x .	x x .	x x .	x x x .	x	
	Ø 1900 mm*	74.8"	234	15.736	11.0 / 24.2	763.	x x .	x x .	x x .	x x .	x x x .	x	
*CRI > 80													
LED 24V CRI > 90 *CRI > 80		Warm-white	3000 K	(Standard)	x x x .	63.	x x .	x x .	x x .	x x .	x x x .	x	
		Neutral-white	4000 K	(Optional)	x x x .	69.	x x .	x x .	x x .	x x .	x x x .	x	
		Extra warm-white	2700 K	(Optional)	x x x .	61.	x x .	x x .	x x .	x x .	x x x .	x	
		Extra warm-white	2200 K*	(Optional)	x x x .	22.	x x .	x x .	x x .	x x .	x x x .	x	
Dimming		Dimmable 0 - 10 V		(Standard)	x x x .	x x .	51.	00.	x x .	x x x .	x		
		DMX		(Optional)	x x x .	x x .	31.	00.	x x .	x x x .	x		
		LUTRON (contact factory)		(Optional)	x x x .	x x .	71.	00.	x x .	x x x .	x		
		Dimmable CASAMBI Bluetooth 4.0 remote control through app. Available Starting 3 rd quarter 2017		(Optional)	x x x .	x x .	81.	00.	x x .	x x x .	x		
Finishes		(Standard) 11 white											
		(Optional) 22 aluminum polished		27 brush-finished aluminum		30 anthracite		32 crocodile black		33 sand silver fine textured			
			35 gold		36 brass		37 bronze fine textured		38 copper		10 black fine textured		
			XX Custom finish										
Power Supply Cable (Standard)		000 without Mounting Version J									000	x	



INSIEME




Housing: Pendant with light distribution up, out and down. 3 circular aluminum profiles, with integrated acrylic covers.

Design: MARKUS BISCHOF



Mounting Version



6 current-carrying steel cables canopy and external power supply unit in suspended ceiling

Item No.	LED	Dimming	LED	Finishes	Power Supply cable	Mounting Version
X X X.	X X.	X X.	X X.	X X.	X X X.	J

J = Distance of external power supply unit to light fixture max. 10m / 394"

Mounting version with 6 current-carrying steel cables 3000mm Including power supply cable 5000mm / 197"

Input voltage for all external power supply units and canopy is 90-277 VAC 47-63 Hz

X X X.	X X.	X X.	X X.	X X.	000	J
--------	------	------	------	------	------------	----------

Complete order number

Dimensions of external power supply units

Typ	Size mm / inch	For use with Mounting Version
DE 2F	360 x 300 x 85 mm / 14.2 x 11.8 x 3.3"	J

+ Canopy as connection

DB 350	Ø 350 / 320 mm / 13.7 x 12.6"	J
	H 60 mm / 2.3"	

Canopy finish: white (11)
contact factory for other finishes
USA/Canada: Canopy mounts to 4" octagonal junction box.



CASAMBI wall-switch

**white
black**

**207. 00. 00. 00. 11
207. 00. 00. 00. 10**

Casambi wall-switch is a wireless user interface that can be configured via the Casambi app. The four target buttons can control a scene or an animation of the user's choice or simply one luminaire, one luminaire group or all lights together if so desired. Up to 4 groups may be separately programmed. It comes with a wall mounting plate. The switch can be attached to the plate as it is equipped with magnets.

