


SATTLER

FAVO THE LIGHT NET

Housing: Thermally conductive thermoplastic
Design: blocher partners



							Item No.	LED	Dimming	LED	Finishes	Power supply Cable	Mounting version
							1750.	40.	08.	00.	68.	Z73.	0A



Direct



Indirect

Light node direct / indirect Ø 70 mm / 2.7"


Direct: 18° beam angle of each lens, 3 x spots with 200 lumens each
Lens arrangement 120° radially, 30° inclination angle
4000 K, CRI > 90, 36V

7,5 Watt - 600 lumens




Indirect: 180° beam angle of lens
4000 K, CRI > 90, 36V

0,5 Watt - 40 lumens



Honeycomb

693 x 800 mm
6 x light nodes per 8 Watt / 640 lumens
= 48 Watt / 3840 lumens



Dimming



Dimming only via Sattler Bluetooth-Control

A permanent internet connection and a mobile device with LE 4.1 or higher as a gateway are required for control

Finishes



68
anthracite

Power supply Cable





Z 73
black, textile

Dimensions of external power supply units			
Type	Size mm / inch	For use with Mounting Version	
	L W H		
DE 1F	360 x 150 x 85 mm / 14.2 x 5.9 x 3.3"	A	
max. 40 light nodes per power supply unit			


Input voltage for all external power supply units is **90-277 VAC 47-63 Hz**

Configuration variant A





Viewing direction / LIGHT NET orientation

LIGHT NET dimensions




Configuration variant B



Viewing direction / LIGHT NET orientation

LIGHT NET dimensions



Distance of external power supply unit to light fixture max. 10m / 394".

Suspension height: 2800 - 3200mm / 110 - 129". Including steel cable suspension 3000mm/118" and power supply cable 5000mm/197"

Optional: Mounting-Set - consisting of steel cables and steel cable grippers for flexible adjustment of the suspension height at the luminaire, **Item No.: 331.00.00.00.00**



Handcrafted in Germany, certified quality



Conforms to UL-STD 1598 Certified to CSA-STD C22.2 No.250.0-08



Light distribution direct/indirect



Protection class III: only suitable for very low voltage supply (<50V)



Luminaires are suitable for mounting on ordinary flammable materials, which have an inflammation point of at least 200° C / 392° F

Technical data is subject to change. Errors and omissions excepted 1) Net lumen output: Losses due to diffusers and reflectors are considered. Lumen values refer to an ambient temperature of max. 35° C / 95° F. 2) Weight of lights without remote technical unit or canopy.